



safetykleen

# brakokleen™



**Effective  
and safe**  
cleaning of  
fibreglass resin  
application  
tools



- PRODUCTIVITY**  
Effective cleaning extends roller life,  
reducing consumption levels by 75%
- QUALITY**  
Rollers immediately ready for re-use  
without any risk to quality
- COMPLIANCE**  
Non-flammable cleaning fluid not  
classed as hazardous, driving lower  
VOC's levels and improving working  
environment



## TYPICAL APPLICATION

Resinkleen™ is an innovative service developed by Safetykleen for fibreglass product manufacturers looking for a safe and effective solution for the cleaning of brushes, rollers and mixing equipment used in the application of resins and gel coats.

## TYPICAL TOOLS TO CLEAN

Resinkleen offers a cost-effective, non-flammable and low VOC content alternative to Acetone delivering improved cleaning performance, extending the life of brushes and rollers:



• Rollers

• Brushes

• Tools

## WHY CHOOSE RESINKLEEN?



### ADAPTABILITY

Compact tank design, robustly manufactured in stainless steel that can be located "in-process" adjacent to individual process cells or centrally located to serve multiple cells



### INNOVATION

Innovative, non-flammable, non-hazardous ester-based organic solvent with a unique anti-gelling chemistry that offers full resin compatibility



### PERFORMANCE

Cleaning fluid dissolves the resin adhered to the brushes or rollers



### PRECISE

The large cleaning submersion area, drying rack and post-cleaning centrifuge dryer ensures that rollers are quickly & efficiently cleaned and ready for re-use

- Large cleaning submersion area and drying rack
- Post-cleaning centrifuge dryer for rapid surplus cleaning fluid removal
- Industry standard safety features
- Robust, stainless steel shell complete with dual lid openings
- Foot pedal control

## SPECIFICATIONS

|                            |                        |
|----------------------------|------------------------|
| Overall Dimensions (HxWxD) | 920 x 920 x 600 mm     |
| Chemistry                  | Resinkleen             |
| Dryer speed                | 1700 rpm (max)         |
| Power Requirements         | Compressed Air (6 bar) |
| Sump Capacity              | 60 litres              |

Improved working environment with reduced VOC levels, enhancing green credentials. Reduced waste disposal as rollers can be re-used rather than discarded, new "Fluffy" roller & brush purchases reduced by up to 75%. Process operating costs reduced by up to 30%. Non-flammable safe cleaning can reduce insurance premiums.

All supported by our specialist chemistry and Fully Serviced Machine program.

