



safetykleen

rustkleen™ ultra



Performance
of Rustkleen
with the **speed**
& **power** of
ultrasonic



PRODUCTIVITY

Virtually no operator involvement required with the instant action of ultrasonic de-rusting

QUALITY

Consistently outstanding results delivered time and again with no change in performance between service points

COMPLIANCE

Not classed as hazardous the Rustkleen solution prevents the need to use highly controlled chemicals including acids and alkalis creating a safer working environment



Small
M257



Large
M258

TYPICAL APPLICATION

Rustkleen ultra™ combines the performance of Rustkleen with the power of ultrasonic to deliver rapid rust removal for all parts. It accelerates the rust removal process using sonically generated pressure waves that agitate the rust removal fluid at very high velocity to cause micro-explosions known as cavitations.

TYPICAL COMPONENTS

Rustkleen chemistry is a safe, water based neutral pH solution that uses a specifically developed blend of molecules to completely remove rust whilst ensuring that even delicate features, plastics and rubbers are not affected during the process:



WHY CHOOSE RUSTKLEEN ULTRA?



PERFORMANCE

The instant action of Ultrasonic technology speeds up the de-rusting process to give a fast turn-around of parts ready for re-processing



ENVIRONMENTAL

No acids, alkalis or noisy mechanical methods. Solution not classed as hazardous



PRECISE

Removes rust leaving paint and decorative features intact



ADAPTABILITY

Safe and effective on a wide variety of applications including: Automotive, marine, and off-shore. For restoration, refurbishment or preservation of components

- Instant acting de-rusting results delivered by ultrasonic energy
- Designed to minimise the operator input and allow for greater employee productivity
- Removes the need for hazardous chemicals to be used in the de-rusting process
- Reduces direct and indirect costs associated with removing rust

	Small - M257	Large - M258
Overall Dimensions (HxWxD)	1038 x 870 x 737 mm	1038 x 1361 x 736 mm
Internal Dimensions (HxWxD)	455 x 500 x 362 mm	455 x 1000 x 362 mm
Load mass	Up to 50 kg / basket (single basket)	Up to 50 kg / basket (2 baskets)
Ultrasonic Frequency	58 kHz	
Power Requirements	230-240 V	
Sump Capacity	100 litres	200 litres

Supported by our specialist chemistry and Fully Serviced Machine program.

