



safetykleen

aquakleen™ XL automatic

**Operator
free cleaning**
offering increased
productivity and
efficiency



PRODUCTIVITY

Operator free cleaning allows skilled labour to be utilised in other tasks whilst high quality cleaning takes place



QUALITY

Automated systems provide standardised performance each and every time



COMPLIANCE

No operator exposure to hazardous chemicals or emissions due to enclosed automatic process and Safetykleen's range of unique aqueous detergents that are not classed as hazardous



TYPICAL APPLICATION

If you have a number of parts to clean in a short time frame, or a bulky difficult-to-clean load, an Aquakleen automatic™ parts washer is the perfect answer. Productivity is increased as the operator is free to work on other tasks, typical soils to be cleaned include:

• Oil	• Wax
• Ink	• Grease
• Coolant	• Cutting Fluid

TYPICAL COMPONENTS

Include components with areas difficult to target such as:



• Engine components	• Gearboxes
• Drive mechanisms	• Fixings and fastenings

- Labour saving with minimal operator involvement
- Multiple components washed in one cycle
- Consistent performance provides repeatability and reliable quality
- Minimal fluid usage and low energy consumption
- Steam extraction condenser helps to reduce fluid loss returning fluid to the wash sump at the end of each cycle
- Quick release mechanism allows for different spray bar options to suit application

WHY CHOOSE AQUAKLEEN AUTOMATIC?



PERFORMANCE

Driven baskets assure a consistently high cleaning standard every time, delivering fluid to every part of the component to be cleaned



ADAPTABILITY

Plug and play approach offers greater flexibility of machine offering scalability from medium size tasks to larger and more complex industrial needs



ACCURACY

A choice of aqueous chemistry allows the most appropriate selection for the application and environmental compliance



LOW ENERGY

Insulated machines providing the lowest electricity consumption available on the market preventing wasted time and energy

	XLarge - M320
Overall Dimensions (HxWxD) open	2670 x 2360 x 2280 mm
Overall Dimensions (HxWxD) closed	2285 x 2360 x 2280 mm
Usable Dimensions	600 x 1400 Ø mm
Max load bearing	1000 kg
Power Requirements	400 V (3 phase)
Sump Capacity	400 litres

Safetykleen's Aquakleen automatic range combine the latest aqueous chemistry with efficient machines to save you time and ensure compliant parts washing processes.

All supported by our specialist chemistry and Fully Serviced Machine program.

